

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
17 February 2005 (17.02.2005)


PCT

(10) International Publication Number  
**WO 2005/015645 A1**

- (51) International Patent Classification<sup>7</sup>: **H01L 31/02, 31/032**
- (21) International Application Number: **PCT/SE2004/001173**
- (22) International Filing Date: **9 August 2004 (09.08.2004)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:  
**0302206-8 12 August 2003 (12.08.2003) SE**
- (71) Applicant (for all designated States except US): **SANDVIK AB [SE/SE]; S-811 81 Sandviken (SE).**
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **SCHUISKY, Mikael [SE/SE]; Mossvägen 75C, S-811 34 Sandviken (SE). CEDERGREN, Magnus [SE/SE]; Furuvägen 6, S-811 36 Sandviken (SE).**
- (74) Agent: **MELIN, Linda; Sandvik AB, Intellectual Property, S-811 81 Sandviken (SE).**
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): **AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.**
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): **ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).**

[Continued on next page]

(54) Title: **NEW METAL STRIP PRODUCT**



(57) Abstract: A coated steel product comprises a metallic strip material which has a coating comprising an electrically insulating layer doped with sodium. The thermal expansion coefficient of said metallic strip material is less than  $12 \cdot 10^{-6} \text{ K}^{-1}$  in the temperature range 0-600°C. Said product may be coated with an electrically conducting layer of molybdenum. The coated steel product is useful as a substrate for flexible Cu (In, Ga) Se<sub>2</sub> (CIGS) solar cells.



**Published:**

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*